

DATA SHEET

PEACOC[®] SMALL TERMINAL 360

The PEACOC Small Terminal 360 (ST360) offers high density fiber management in an extremely small, yet easily accessible enclosure for quick turn-up of field connections. PEACOC spreadable adapter technology provides ample handling space for safe, fast, and error-free installation of drop cables. The internal, rotating cable spool holds up to 120 feet of stub cable for quick deployment or convenient slack storage. For plug-and-play operability and reduced labor costs, the cable stub can be factory terminated with an MPO connector. The PEACOC ST360 helps fiber networks work smarter, not harder, saving time and money.



Benefits:

- Improves turn-up accuracy due to easy fiber access without disruption of other fibers
- Speeds installation and reduces labor costs with MPO plug-and-play connections
- Saves space with small footprint and built-in slack storage capabilities



Features:

- High capacity in a compact size (up to 12 SC or 24 LC drop ports)
- PEACOC spreadable adapter technology for enhanced connector access
- Pre-stubbed tail lengths up to 1,000 ft with an option for MPO termination
- Internal spool deploys/stores up to 120 ft of 3.0mm fiber cable
- IP63 rated for indoor installation

Applications:

- Suitable for use in any fiber network
- FTTA, MDU, and customer premise applications

SPECIFICATIONS

Attributes	Specifications
Drop Port Capacity	Up to 12 SC / 24 LC
Supported drop cables	3.0mm Round
Adapter Type(s)	LC/APC & LC/UPC Duplex, SC/APC & SC/UPC Simplex
Internal Cable Spool Capacity	Up to 120 ft of 3.0mm cable or 75 ft of 3.8mm cable
Locking Mechanism	Standard Phillips Head Screw
Color	White
Operating Temperature	-40°C to +65°C
Mounting Options	Wall Mount
Standards	IP63, ETL
Outer Dimensions	5.9 in x 7.9 in x 3.7 in

PRODUCT DIMENSIONS



ORDERING INFORMATION



4 Stub Connector

Code	Code Description
M	MPO
C	None

5-6 Number of Drop Ports

Code*	Code Description
06	6 Ports
12	12 Ports
16	16 Ports
24	24 Ports

*Maximum of 12 ports for SC or 24 ports for LC

7 Adapter Type

Code	Code Description
1	LC/UPC Duplex
2	LC/APC Duplex
3	SC/UPC Simplex
4	SC/APC Simplex

8 Stub Cable Type

Code	Code Description
A	12F 3.0mm Riser Rated
B	12F 3.0mm Plenum Rated
C	24F 3.8mm Riser Rated
D	24F 3.8mm Plenum Rated

10-12 Stub Cable Length

Code*	Code Description
---	3-Digit Length

*50 to 1000 ft (50 ft increments)

9 Unit of Length

Code	Code Description
F	Feet
M	Meters



GoFoton
 28 World's Fair Drive
 Somerset, NJ 08873
 gofoton.com
 732.469.9650

GoFoton
 Innovator. Expert. Problem Solver.

© 2024, GoFoton, all rights reserved.
 DS-ST3-091524
 Specifications are subject to change without notice.